#99-024 **Material Safety Data Sheet** U.S. Department of Labor Occupation Safety and Health Administration 45-050-006 May be used to comply with OSHA's Hazard Communication Standard (Non-Mandatory Form) 29 CFR 1910.1200. Standard must be Form Approved Rdk Inner Secret Perm consulted for specific requirements OMB No. 1218-0072 Note: Blank spaces are not permitted. If any item is not applicable, or no IDENTITY information is available, the space must be marked to indicate that. Anhydrous Perm Wave Waving/Reforming Lotions Section I Manufacturer's Name Emergency Telephone Number L'Oreal USA Products, Inc. (800) 535-5053 (Int'l 352-323-3500) Address (Number, Street, City, State, and ZIP Code) Telephone Number For Information 111 Terminal Avenue (732) 499-2745 Date Prepared Clark, NJ 07066 December 18, 2003 Signature of Preparer (optional) GCD

Section II - Hazardous Ingredients/Identity Information

· · · · · · · · · · · · · · · · · · ·				
		ACGIH	Other Limits	
Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	TLV	Recommended	% (optional)

Glyceryl Monothioglycolate

None

~75%

Boiling Point	Specific Gravity (H2O = 1)		
	N/A		~1.2
Vapor Pressure (mm Hg)		Melting Point	
	N/A		N/A
Vapor Density (AIR = 1)		Evaporation Rate	
	>1	(Butyl Acetate = 1)	<1

Insoluble

Appearance and Odor

Thick viscous liquid with a sulfurous odor.

Section IV - Fire and Explosion Hazard Data						
Flash Point (Method Used)	Flammable Limits	LEL	UEL			
>200°F (closed cup)	None	N/A	N/A			

Extinguishing Media

Carbon dioxide, dry chemical, foam, and/or water spray.

Special Fire Fighting Procedures

For small fires, use carbon dioxide, dry chemical, or foam.

For larger fires, use ample quantities of water. Wear a self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Material may undergo decomposition into hydrogen sulfide and oxides of sulfur in a fire.

Section V - R	eactivity Data			#99-024
Stability	Unstable		Conditions to Avoid	
	Stable	X	Avoid excessive h	neat.
Incompatibility (M	aterials to Avoid)			
Metallic st	irrers and b	owls, i	ron, nickel, oxidizing agents, a	and acids.
Hazardous Decor	nposition or Byprodu	cts		
Hydrogen su	ılfide, sulfu	ır dioxi	de, sulfur trioxide.	
Hazardous	May Occur		Conditions to Avoid	
Polymerization	Will Not Occur	X	None known.	
Section VI - H	lealth Hazard Da	ata		
Route(s) of Entry:		Inhalation?	Skin?	Ingestion?
		Yes	Yes	Not likely.

Health Hazards (Acute and Chronic)

Harmful if swallowed, inhaled, or absorbed through skin. This product may cause serious irritant, respiratory, and/or allergic reactions in sensitive individuals.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure

Irritation of eyes, skin, and mucous membranes. Possible irritant/allergic dermatitis and respiratory signs and symptoms, the onset of which may be delayed.

Medical Conditions Generally Aggravated by Exposure

Existing dermatological conditions, such as eczema, and respiratory conditions, such as bronchial asthma and/or chronic bronchitis, may be exacerbated.

Emergency and First Aid Procedure

If swallowed, call a physician, hospital emergency room, or poison control center immediately. Induce vomiting only if recommended by medical personnel. Get prompt medical attention. If affected by inhalation, move to fresh air. If symptoms persist, get medical attention. If eye or skin contact occurs, immediately flush with water and get medical attention if irritation occurs.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Dike and contain the free liquid, if any, and absorb on vermiculite, spill pillows, or other suitable absorbant material. Place spent absorbants in proper containers for disposal.

Waste Disposal Method

This material is not regulated under RCRA. Accordingly, incineration at a non-hazardous waste treatment facility is the preferred method of disposal.

Precautions to be Taken in Handling and Storage

Use only with adequate ventilation and avoid inhalation. Avoid contact with eyes and skin (other than areas of application). Do not inhale or ingest. Prepare and use in a well-ventilated area. To assure maximum shelf-life, avoid direct sunlight.

Other Precautions

For external use only. Use only as directed. Keep out of reach of children. Patch test is intended to identify skin reaction only; it will not necessarily predict sensitization or irritation secondary to inhalation. Read the product package insert completely.

Respiratory Protection (Specify Type)

For manufacturing/filling, wear a NIOSH-approved respirator if constitutent TLVs are exceeded. For spill management, use an approved self-contained breathing apparatus. For product use, respiratory protection is generally unnecessary.

Ventilation	Local Exhaust	Recommended	Special	
	Mechanical(General)	Generally	Other	
		Acceptable		

Protective Gloves

Plastic or rubber gloves.

Other Protective Clothing or Equipment

Safety glasses with side shields and protective clothing for bulk quantities.

Work/Hygienic Practices

OSHA hazard classification: Irritant, slightly toxic, possible sensitizer.

DOT classification: Bulk - Not regulated.

Finished Product - Not regulated.

Forms published by ChemSW (707)864-0845