

4318083

60175000
s53354b

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

June 6, 2012
10:54

C H R Y S L E R
HAZARD COMMUNICATION SHEET

58658 PART/COMMTY CD: 04318083
PREPARATION DATE: 08-25-10 STNDRD: MS-CD920, 98 SUPPLIER: 24378 MFGR: 03500
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: MOPAR GASKET MAKER
MFG ID : 518
DESCRIPTION: SEALANT-GASKET MAKER

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS: PERCENT
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS
EXISTING INGREDIENTS
ACRYLIC ACID 5-10 W 10 2 2 PPM S
000079-10-7 2-PROPENOIC ACID (9C T
SILICA, AMORPHOUS (FUMED) 5-10 W 6 10 6 MG/M3
007631-86-9 SILICA (8CI9CI)
TDI-BASED POLYURETHANE METHACRYLA 60-100 W N/AV N/AV N/AV N/AV
037187-00-1C POLYURETHANE METHACR
POLYETHYLENE GLYCOL DIMETHACRYLAT 5-10 W N/AV N/AV N/AV N/AV
025852-47-5 POLY(OXY-1,2-ETHANED
CUMENE HYDROPEROXIDE 1-5 W N/AP N/AP N/AP N/AP
000080-15-9 HYDROPEROXIDE, 1-MET T
ETHYLENE GLYCOL 1-5 W N/AP N/AP N/AP N/AP
000107-21-1 1,2-ETHANEDIOL (9CI) T
C 50 39 50
SACCHARIN 0.1-1.0 W N/AP N/AP N/AP N/AP
000081-07-2 1,2-BENZISOTHIAZOL-3
BALANCE:
HYDRACETIN/CUMENE/
GENERIC DESC: GASKET MIXTURE OF RESIN, ACTIVATOR, FILLERS, AND ORGANIC
SOLVENTS.

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : > 300 F SOLUB IN WATER: SLIGHT (0.1 - 1%)
Page 1 of 4

Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP

VAPOR PRESSURE: < 5 MM HG AT 70 F EVAP. RATE: N/AV REF: N/AV
VAPOR DENSITY : N/AV SPECIFIC GRAVITY: 1.100 AT 70 F
PH AT FULL STRENGTH: N/AP PH AT REC. DILUT: N/AP
%VOLATILE BY VOL : < 10.0 VOLATILE ORGANIC COMP: N/AV N/AV
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV
APPEARANCE & ODOR: COLOR: RED..... STATE: GEL.....-ODOR: SHARP,
IRRITATING.....

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

FLASH POINT: 200 F N/AV IGN TEMP: N/AP LEL: N/AV UEL: N/AV
SPECIAL FIRE & EXPLOSION HAZARDS:

RELEASES TOXIC FUMES OR GASES WHEN HEATED TO DECOMPOSITION.

EXTINGUISHING MEDIA:

CARBON DIOXIDE, FOAM OR DRY CHEMICAL.

SPECIAL FIREFIGHTING PROCEDURES:

USE SELF-CONTAINED BREATHING APPARATUS FOR ENCLOSED AREAS. USE WATER TO
COOL FIRE EXPOSED CONTAINERS. REMOVE CONTAINERS FROM FIRE AREA IF POSSIBLE.

SENSITIVE TO MECHANICAL IMPACT?: N/AV SENSITIVE TO STATIC DISCHARGE?: N/AV

HAZARDOUS COMBUSTION PRODUCTS:

OXIDES OF CARBON, NITROGEN AND IRRITATING ORGANIC VAPORS.

FLAME PROJECTION: N/AP

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---INGESTION--->> MAY BE HARMFUL OR FATAL IF SWALLOWED. MAY PRODUCE THE
FOLLOWING: KIDNEY DAMAGE AND ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED
BY HEADACHE, DIZZINESS, STAGGERING, CONFUSION, UNCONSCIOUSNESS OR COMA.

<<---EYE CONTACT--->> VAPOR MAY PRODUCE THE FOLLOWING: IRRITATION AND
TEARING. DIRECT CONTACT MAY PRODUCE THE FOLLOWING: BURN AND BLINDNESS.

<<---SKIN CONTACT--->> PROLONGED CONTACT MAY PRODUCE THE FOLLOWING: SEVERE
IRRITATION. CHRONIC EXPOSURE MAY PRODUCE THE FOLLOWING: DERMATITIS.

<<---INHALATION--->> VAPOR MAY PRODUCE THE FOLLOWING: NASAL IRRITATION

<<---SPECIAL TOXICITY--->> MAY CAUSE REPRODUCTIVE EFFECTS. MAY PRODUCE THE
FOLLOWING: BLOOD ABNORMALITIES AND LIVER DAMAGE. COMPONENTS HAVE BEEN SHOWN
TO CAUSE TUMORS IN ANIMALS.

EMERGENCY FIRST AID PROCEDURES:

<<---INGESTION--->> DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY. KEEP
WARM AND QUIET. <<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE
AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE
FOR 15 MINUTES. CONTACT A PHYSICIAN. <<---SKIN CONTACT--->> REMOVE
CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF CONDITION PERSISTS,
CONSULT A PHYSICIAN. <<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. IF
CONDITION PERSISTS, CONSULT A PHYSICIAN.

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

*** SECTION 06 - REACTIVITY DATA ***

STABILITY: STABLE

CONDITIONS TO AVOID:

NONE KNOWN.

MATERIALS TO AVOID:

NONE KNOWN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN AND IRRITATING ORGANIC VAPORS.

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

WIPE UP OR SCRAPE UP SMALL SPILL OR RESIDUE. DISPOSE OF WASTE IN A CLOSED HALF-FILLED CONTAINER. DO NOT MIX WITH OTHER WASTE OR SUBSTANCES.

RESIDUE-WIPE UP RESIDUE WITH SOLVENT SUCH AS ISOPROPYL ALCOHOL.

WASTE DISPOSAL METHODS:

INCINERATE OR DISPOSE OF IN A LANDFILL. DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL REGULATIONS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. DUST AND MIST RESPIRATOR. THIS EQUIPMENT MAY BE NEEDED FOR GRINDING, SANDING OR OTHER OPERATIONS WHICH GENERATE DUST..

VENTILATION TYPE:

LOCAL EXHAUST VENTILATION. THIS EQUIPMENT MAY BE NEEDED IF THE ALLOWABLE LIMIT OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED..

PROTECTIVE GLOVES:

RECOMMENDED. RUBBER GLOVES OR PLASTIC GLOVES.

EYE PROTECTION:

RECOMMENDED. SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. APRON (SAME MATERIAL AS GLOVES).. THIS EQUIPMENT MAY BE NEEDED TO AVOID PROLONGED SKIN CONTACT..

*** SECTION 09 - SPECIAL PRECAUTIONS ***

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE AT TEMPERATURE BELOW 110 F (43 C). USE WITH ADEQUATE VENTILATION. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED, SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID). DANGER,

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

CANCER SUSPECT AGENT.

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING VAPOR. AVOID EYE CONTACT. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID INGESTION. WASH THOROUGHLY AFTER HANDLING. MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP
NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

WASTE CODE(S)/HZD: | MICH: N/AP

THE ABOVE INFORMATION IS BASED ON DATA PROVIDED BY SUPPLIERS. TESTING IS NOT NEEDED