60175000 s53354b

FILLER.

Global Parts Order Processing Material Safety Data Sheet MORAN ST. CLAIR CHRYSLER JEEP

May 30, 2012 16:37

CHRYSLER

HAZARD COMMUNICATION SHEET 2002094 PART/COMMTY CD: 04761863 PREPARATION DATE: 05-02-06 STNDRD: N/AV SUPPLIER: 37304 MFGR: 03500 OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES *** SECTION 01 - PRODUCT INFORMATION *** MFG BY: PART SALES & SERVICE CHRYSLER 26311 LAWRENCE AVE CENTERLINE MI 48015 EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888 DIST BY: PART SALES & SERVICE CHRYSLER 26311 LAWRENCE AVE CENTERLINE MI 48015 EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888 CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888 BRAND NAME: MOPAR FINISH RESTORER - LIGHT MFG ID : N/AV DESCRIPTION: CLEANER-FINISH RESTORER - LIGHT *** SECTION 02 - INGREDIENTS *** HAZARDOUS INGREDIENTS: PERCENT COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS ***EXISTING INGREDIENTS*** ATMOSPHERIC GAS OIL (PETROLEUM) 10-30 W 400 N/AP 400 PPM 064741-41-9 NAPHTHA, PETROLEUM, DISTILLATES (PETROLEUM), ACID-TRE 10-30 W 5 5 MG/M3 064742-14-9A DISTILLATES (PETROLE L N/AP 10 DIATOMACEOUS SILICA, CALCINED 1-5 W 6 10 6 MG/M3 061790-53-2 KIESELGUHR ZEOLITE 1-5 W 0.500 0.500 0.500 MG/M3 066402-68-4 CERAMIC MATERIALS AN 1-5 W 10 10 10 MG/M3 GLYCERINE 000056-81-5 1,2,3-PROPANETRIOL (DISTILLATES (PETROLEUM), HYDROTRE 5-10 W 5 5 5 MG/M3 064742-46-7A DISTILLATES (PETROLE L N/AP 10 10 MINERAL OIL 1-5 W 5 5 5 MG/M3 I1 N1 008012-95-1 PARAFFIN OILS L N/AP 10 10 KAOLINITE (H4AL2SI2O9) (9CI) 1-5 W N/AP N/AP N/AP 001318-74-7 KAOLINITE (AL2(SI207 VEGETABLE OIL(S) 1-5 W N/AV N/AV N/AV 003669-00-5C VEGETABLE OIL(S) WATER 60-100 W N/AP N/AP N/AP N/AP 007732-18-5 WATER (8CI9CI) GENERIC DESC: CONTAINS WATER, PETROLEUM DISTILLATES, MILD ABRASIVES, OILS AND

Global Parts Order Processing Material Safety Data Sheet MORAN ST. CLAIR CHRYSLER JEEP

*** SECTION 03 - PHYSICAL DATA *** ______

SOLUB IN WATER: APPRECIABLE (> 10%) BOILING POINT : > 380 F

VAPOR PRESSURE: < 10 MM HG AT 70 F EVAP. RATE: < 1.000 REF: N/AV

SPECIFIC GRAVITY: 1.050 AT N/AV VAPOR DENSITY : > 1.000 AT N/AV

PH AT FULL STRENGTH: PH AT REC. DILUT: N/AP 6.0

%VOLATILE BY VOL : < 18.0 VOLATILE ORGANIC COMP: N/AV N/AV

ODOR THRESHOLD: N/AV PPM FOR % POPULATION

COEFF. OF WATER/OIL DIST: N/AV FREEZING POINT: N/AV

APPEARANCE & ODOR: COLOR: CREAM..... OR APPEARANCE: LIGHT..... COLOR:

GREEN.... STATE: LIQUID.... WITH THE FOLLOWING: ODOR:

SWEET

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

_____ FLASH POINT: > 200 F PMCC IGN TEMP: N/AV LEL: N/AP UEL: N/AP

SPECIAL FIRE & EXPLOSION HAZARDS:

WHEN HEATED TO DECOMPOSITION MAY PRODUCE TOXIC THERMAL DECOMPOSITION PRODUCTS. MAY REACT WITH OXIDIZERS.

EXTINGUISHING MEDIA:

DRY CHEMICAL, FOAM OR CARBON DIOXIDE.

SPECIAL FIREFIGHTING PROCEDURES:

USE PROTECTIVE CLOTHING. AVOID BREATHING VAPOR OR FUMES. USE SELF-CONTAINED BREATHING APPARATUS.

SENSITIVE TO MECHANICAL IMPACT?: NO SENSITIVE TO STATIC DISCHARGE?: NO

HAZARDOUS COMBUSTION PRODUCTS:

CARBON MONOXIDE AND CARBON DIOXIDE.

FLAME PROJECTION: N/AP

*** SECTION 05 - HEALTH HAZARD DATA ***

._....

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<---INHALATION--->> VAPOR-MAY BE IRRITATING TO EYES, NOSE, AND THROAT.

<---SKIN CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: MINOR

IRRITATION. PROLONGED SKIN EXPOSURE MAY RESULT IN THE FOLLOWING: DERMATITIS.

<---EYE CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: IRRITATION AND TEARING. <<---INGESTION--->> MAY BE HARMFUL IF SWALLOWED.

EMERGENCY FIRST AID PROCEDURES:

<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. IF PULMONARY SYMPTOMS

DEVELOP, CONSULT A PHYSICIAN. <----SKIN CONTACT--->> WASH WITH SOAP AND

WATER. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <---EYE CONTACT--->>

RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING

BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. IF CONDITION PERSISTS,

CONSULT A PHYSICIAN. <---INGESTION--->> DRINK LARGE QUANTITIES OF WATER. DO

NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY.

Global Parts Order Processing Material Safety Data Sheet MORAN ST. CLAIR CHRYSLER JEEP

STABILITY: STABLE CONDITIONS TO AVOID: NONE KNOWN. MATERIALS TO AVOID: STRONG OXIDIZING AGENTS. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR POLYMERIZATION CONDITIONS TO AVOID: POLYMERIZATION WILL NOT OCCUR. HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION MAY PRODUCE THE FOLLOWING: CARBON MONOXIDE AND CARBON DIOXIDE *** SECTION 07 - SPILL OR LEAK PROCEDURES *** _____ STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: WIPE UP OR SCRAPE UP SMALL SPILL OR RESIDUE. LARGE SPILL-CONTAIN WITH DIKE. ABSORB ON AN INERT MATERIAL. DISCARD INTO SEALED CONTAINERS FOR DISPOSAL. WASTE DISPOSAL METHODS: DISPOSE OF ABSORBANT IN A LANDFILL. DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL REGULATIONS. ______ *** SECTION 08 - SPECIAL PROTECTION *** RESPIRATORY PROTECTION: NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. **VENTILATION TYPE:** GOOD GENERAL VENTILATION AND/OR LOCAL EXHAUST VENTILATION. THIS EQUIPMENT MAY BE NEEDED TO MAINTAIN THE TLV.. PROTECTIVE GLOVES: NEOPRENE GLOVES.. THIS EQUIPMENT MAY BE NEEDED TO AVOID PROLONGED SKIN CONTACT.. EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL GOGGLES. THIS EQUIPMENT MAY BE NEEDED IF THE PRODUCT IS SPLASHED... OTHER PROTECTIVE EQUIPMENT: NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. ______

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE IN A COOL, DRY PLACE. KEEP FROM HEAT, SPARK OR OPEN FLAMES. STORE SEPARATE FROM INCOMPATABLE MATERIALS. REACTS WITH OXIDIZERS. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

*** SECTION 09 - SPECIAL PRECAUTIONS ***

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING VAPOR. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID EYE CONTACT. AVOID INGESTION. WASH THOROUGHLY AFTER HANDLING. REMOVE Page 3 of 4

60175000 s53354b

Global Parts Order Processing Material Safety Data Sheet MORAN ST. CLAIR CHRYSLER JEEP

🕶 د ۽ پ

May 30, 2012 16:37

CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#:

HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP

NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

WASTE CODE(S)/HZD:

| MICH: N/AP

THE ABOVE INFORMATION IS BASED ON DATA PROVIDED BY SUPPLIERS. TESTING IS NOT

NEEDED