ITEM: 5TP99 - Maintenance Absorbent 20 lb. Pail

ORDER: 0140173461

LP NUMBER: U251878271-A

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the res	spective product with which it is associated.
<u> </u>	######################################
MATERIAL SAFETY DATA SHEET - C3375	5. FIREFIGHTING MEASURES

Associated Grainger Items 1KKM7, 24X070, 24X071, 3YFA7, 4UB34, 5TP99

OTT-DRT CORPORATION OF AMERICA 410 NORTH MICHINGAN AVENUE CHICAGO, IL 60611

MSDS: C3375

MATERIAL SAFETY DATA SHEET

GRANULAR ABSORBENT (#1003000)

(312) 321-1515, INFORMATION

(800) 424-9300, EMERGENCY

- 1. PRODUCT IDENTIFICATION

MSDS NUMBER: 1003000

IDENTITY: GRANULAR ABSORBENT

ISSUED: JULY 5, 2011

CHEMICAL NAME: FULLERS EARTH AND/OR BENTONITE OR AMORPHOUS OPALINE SILICA

- 2. COMPOSITION -

COMPONENT CAS NUMBER AMOUNT SILICA HYDRATED (AMORPHOUS OPALINE SILICA) 7631-86-9 90-100% FULLERS FARTH 8031-18-3 90-100% 1302-78-9 90-100%

OUARTZ (RESPIRABLE <1%) 14808-60-7 <10% BULK

3. HAZARDS IDENTIFICATION -

EMERGENCY OVERVIEW:
THIS PRODUCT IS A NON-COMBUSTIBLE, CHEVICALLY INERT MINERAL. THIS MINERAL
SAMPLE CONTAINS NATURALLY-COCURRING CRYSTALLINE SILICA AS QUARTZ. PROLONGED
OVEREXPOSURE TO RESPIRABLE CRYSTALLINE SILICA MAY CAUSE LUNG DISEASE
(SILICOSIS). LARC, IN MONOGRAPH 68, HAS CONCLUDED THAT CRYSTALLINE SILICA
INHALED IN THE FORM OF QUARTZ FROM OCCUPATIONAL SOURCES IS CARCINOCENIC TO
HUMANS (GROUP 1); HOWEVER, CARCINOGENICITY WAS NOT DETECTED IN ALL
INDUSTRIAL CIRCLMSTANCES STUDIED. THE COMPANY IS NOT AWARE OF ANY SCIENTIFIC
OR MEDICAL DATA AVAILABLE INDICATING THAT EXPOSURE TO DUST FROM THIS PRODUCT
UNDER CONDITIONS OF NORMAL USE WILL CAUSE SILICOSIS OR CANCER. ADVERSE
EFFECTS WOULD NOT BE EXPECTED FROM NORMAL USE OF THIS PRODUCT.

INGESTION: NO ADVERSE EFFECTS EXPECTED WITH UNUSED MATERIAL.

INHALATION OF EXCESSIVE CONCENTRATIONS OF DUST MAY CAUSE IRRITATION OF MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT.

EYE: CONTACT MAY CAUSE MECHANICAL IRRITATION AND POSSIBLE INJURY.

SKIN: NO ADVERSE EFFECTS EXPECTED.

SENSITIZATION: NO ADVERSE EFFECTS EXPECTED.

CHRONIC/CARCINOGENICITY:
INHALATION OF EXCESSIVE CONCENTRATIONS OF ANY DUST, INCLUDING THIS MATERIAL,
MAY LEAD TO LUNG INJURY. THIS PRODUCT CONTAINS CRYSTALLINE SILICA. EXCESSIVE
INHALATION OF RESPIRABLE CRYSTALLINE SILICA MAY CAUSE SILICOSIS, A
PROGRESSIVE, DISABLING AND FATAL DISEASE OF THE LUNG. SYMPICMS MAY INCLUDE
COUGH, SHOKINESS OF BEREITH, WHEEZING AND REDUCED PULNONDRY FUNCTION. THE
INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC), IN MONOGRAPH 68 HAS
CONCLUDED THAT CRYSTALLINE SILICA INHALED IN THE FORM OF QUARTZ OR
CRISTOBALITE, FROM OCCUPATIONAL SOURCES IS CARCINOGENIC TO HUMANS (GROUP 1).
HOWEVER, IN MAKING THE OVERALL EVALUATION, THE WORKING GROUP OUTED THAT
CARCINOCENICITY WAS NOT DEFECTED IN ALL INDUSTRIAL CURCUMSTANCES STUDIED.
CARCINOCENICITY MAY BE DEPENDENT ON INHERENT CHARACTERISTICS OF THE
CRYSTALLINE SILICA OR ON EXTERNAL FACTORS AFFECTING ITS BIOLOGICAL ACTIVITY
OR DISTRIBUTION OF ITS POLYMORPHS. THE NATIONAL TOXICOLOGY PROGRAM (MITP)
CLASSIFIES CRYSTALLINE SILICA AS A KNOWN CARCINOGEN. THE COMPANY IS NOT
AMARE OF ANY SCIENTIFIC OR MEDICAL DATA AVAILABLE INDICATING THAT EXPOSURE
TO DUST FROM THIS PRODUCT UNDER CONDITIONS OF NORMAL USE
SILICOSIS OR CANCER. ADVERSE EFFECTS WOULD NOT BE EXPECTED FROM MORMAL USE CHRONIC/CARCINOGENICITY:

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE CURRENTLY KNOWN.

----- 4. FIRST ATD MEASURES -

IMMEDIATELY FLUSH EYES WITH COOL RUNNING WATER, LIFTING UPPER AND LOWER LIDS.IF IRRITATION PERSISTS OR FOR FOREIGN BODY IN THE EYE, GET IMMEDIATE MEDICAL ATTENTION.

SKIN: NONE NEEDED FOR NORMAL USE.

THE USED MATERIAL IS INCESTED, GET MEDICAL ATTENTION DUE TO POSSIBILITY OF CHEMICAL CONTAMINATION. IF LARGE AMOUNT OF UNUSED MATERIAL IS SWALLOWED, CHAMEDIATE MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR.

FLASH POINT: THIS PRODUCT IS NOT COMBUSTIBLE.

FLAMMABLE LIMITS: NOT APPLICABLE

EXTINGUISHING MEDIA: USE MEDIA THAT IS APPROPRIATE FOR SURROUNDING FIRE.

UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE

SPECIAL FIREFIGHTING INSTRUCTIONS: MONI; REQUIRED.

HAZARDOUS COMBUSTION PRODUCTS: NONE

6. ACCIDENTAL LUCEASE MEASURES

SWEEP UP AND COLLECT FOR RE-USE OR DISHOSAL-

-- 7. HANDLING AND STORAGE -

HANDLING:

AVOID BREATHING DUST. IF CLOTHING FIXONES DUSTY, LAUNDER BEFORE RE-USE.

STORAGE: STORE IN A DRY AREA.

- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION -

EXPOSURE GUIDELINES:

COMPONENT EXPOSURE LIMIT

SILICA HYDRATED (AMORPHOUS

PEL: 30 MG/M3/%SiO2

OPALINE SILICA) FULLERS EARTH

PEL: 15 MG/M3 TWA (TOTAL DUST) PEL: 5 MG/M3 TWA (RESPIRABLE FRACTION)

BENTONITE

PEL: 15 M3/M3 TWA (TOTAL DUST)
PEL: 1 M3/M3 TWA (RESPIRABLE FRACTION)

PEL: 10 M/M3/%SiO2+2 TWA TLV: 0.025 MG/M3 TWA QUARTZ (RESPIRABLE <1%)

PEL: OSHA PERMISSABLE EXPOSURE LIMIT.

AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH) THRESHOLD LIMIT VALUE.

TWA: 8 HOUR WEIGHTED AVERAGE

STEL: SHORT TERM EXPOSURE LIMIT.

ENGINEERING CONTROLS:
FOR OPERATIONS WHERE THE EXPOSURE LAWAY NAY BE EXCEEDED, LOCAL EXHAUST VENTILATION IS RECOMMENDED.

RESPIRATORY PROTECTION: FOR OPERATIONS WHERE THE EXPOSURE LIMIT MAY BE EXCEEDED, A NIOSH/MSHA APPROVED HIGH EFFICIENCY PARTICULATE RESPIRATOR IS RECOMMENDED.

SKIN PROTECTION: NONE REQUIRED FOR NORMAL USE.

EYE PROTECTION: SAFETY GLASSES OR GOGGLES RECOMMENDED.

OTHER: NONE REQUIRED FOR NORMAL USE.

— 9. PHYSICAL AND CHEMICAL PROPERTIES -

APPEARANCE AND ODOR: GRAY TO TAN (OR RED) GRANULES, NO ODOR

PHYSICAL STATE: SOLID

BOILING POINT: NOT APPLICABLE

VAPOR PRESSURE: NOT APPLICABLE

VAPOR DENSITY: NOT APPLICABLE

SOLUBILITY IN WATER: INSOLUBLE

SPECIFIC GRAVITY: 2.2

pH: NOT APPLICABLE

MELTING POINT: NOT APPLICABLE

OCTANOL/WATER COEFFICIENT: NOT AVAILABLE

— 10. STABILITY AND REACTIVITY —

STABILITY: STABLE

PHYSICAL COMPACT BETWEEN THIS MATERIAL AND TURPENTINE, HYDROFLUORIC ACID, VESETABLE OIL OR OTHER UNSATURATED ORGANIC COMPOUNDS (SUCH AS FISH OIL) M GENERATE HEAT AND/OR FIRE. DO NOT USE THIS MATERIAL WITH THESE COMPOUNDS.

HAZARDOUS DECOMPOSITION PRODUCTS: MONE

HAZARDOUS POLYMERIZATION: WILL NOT COCUR.

- 11. TOXICOLOGICAL INFORMATION -

O-D SAMS PREMIUM POLY OFF SHORE GENERIC OIL DRI 12/24 LVM

OIL DRI ALLPURPOSE
OIL DRI ALLPURPOSE 33 1/3
OIL DRI INDUSTRIAL
OIL DRI INDUSTRIAL ABSORBENT
OIL DRI PREMIUM POLY ABS
OIL DRI REGULAR ABSORBENT PLAIN
OIL DRI U.S. SPECIAL
OIL ZORB
OIL ZORB PREMIUM ABS OIL ZORB PREMIUM ABS
OIL-DRI AUTOMOTIVE PREMIUM 4/10
OIL-DRI PREMIUM POLY ABS
PVL HEAVY DUTY GENERIC
QUICK SORB PAIL
SND STANDARD GB
SUPER CLEAN A.P. 18/40
WHITE ABSORBENT
WHITE ABSORBENT ISSUED ON: JULY 5, 2011