

**Material Safety Data Sheet**

Products associated with this document are exempt from OSHA's Hazard Communication Standard 29 CFR 1910.1200, due to low presence or no presence of hazardous materials. Standard must be consulted for specific requirements and reporting thresholds.

U.S. Department of Labor  
Occupation Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved

Non-Haz

32-050-056

Redken Body Full Instant Bodifier

OMB No. 1218-0072

**IDENTITY**

L'Oreal Non-Hazardous hair styling, cosmetic and/or skin care products

*Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.*

**Section I****Manufacturer's Name**

L'Oreal USA Products, Inc.

**Emergency Telephone Number**

(800) 535-5053 (Int'l 352-323-3500)

**Address (Number, Street, City, State, and ZIP Code)**

111 Terminal Avenue

**Telephone Number For Information**

(732) 499-2745

Clark, NJ 07066

**Date Prepared**

May 10, 2005

**Signature of Preparer (optional)**

CLJ/GCD

**Section II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Not applicable				

**Section III - Physical/Chemical Characteristics**

Boiling Point (Liquids)	varies	Specific Gravity (H <sub>2</sub> O = 1)	>1
Vapor Pressure (mm Hg)	N/A	Melting Point (Solids)	varies
Vapor Density (AIR = 1)	>1	Evaporation Rate (Butyl Acetate = 1)	<1

**Solubility in Water**

Generally soluble or miscible

**Appearance and Odor**

May have a mild to moderate fragrance

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used)	Flammable Limits	LEL	UEL
>200°F	Not applicable	N/A	N/A

**Extinguishing Media**

Carbon dioxide, dry chemical, foam, and/or water spray.

**Special Fire Fighting Procedures**

Fires involving bulk product may be extinguished with carbon dioxide, dry chemical, and/or foam. Water spray may be used to soak corrugated shipping containers of finished product if involved in a fire.

**Unusual Fire and Explosion Hazards**

None; however, observe usual precautions for handling of combustible materials. For manufacturing, minimize airborne vapor levels through engineering controls.

**Section V - Reactivity Data**

Non-Haz

Stability	Unstable		Conditions to Avoid	Avoid heat, fire, and other sources of ignition.
	Stable	X		

## Incompatibility (Materials to Avoid)

Oxidizing agents and nitric acid.

## Hazardous Decomposition or Byproducts

Silicon dioxide, carbon monoxide, carbon dioxide.

Hazardous Polymerization	May Occur		Conditions to Avoid	None known.
	Will Not Occur	X		

**Section VI - Health Hazard Data**

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes

## Health Hazards (Acute and Chronic)

No health hazards anticipated.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

## Signs and Symptoms of Exposure

No health hazards anticipated.

Medical Conditions Generally Aggravated by Exposure
None known.

Emergency and First Aid Procedure
If in eyes, flush with plenty of water for at least 15 minutes. Get medical attention if irritation occurs. If swallowed, drink one or two glasses of water or milk and consult a physician. If on skin, wash with soap and water.

**Section VII - Precautions for Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled
Eliminate all sources of ignition. Dike and contain the free liquid, if any, and absorb on vermiculite, spill pillows, or other absorbants. Containerize spent absorbants in suitable containers for disposal. Wash spill area with detergent solution as necessary.

Waste Disposal Method
Non-hazardous products are not regulated as hazardous wastes when intended for disposal. However, incineration is the recommended method of treatment and disposal for such products.

Precautions to be Taken in Handling and Storage
Store bulk quantities in a cool, well-ventilated room. Limit quantities on hand to the extent possible. Store away from possible sources of ignition. Observe usual precautions relative to static electricity. Avoid oxidizing agents and nitric acid.

Other Precautions
For external use only. Use only as directed.

**Section VIII - Control Measures**

For routine manufacturing/filling operations, none generally required. For spills, wear an approved self-contained breathing apparatus.

Ventilation	Local Exhaust	Explosion-Proof	Special
	Mechanical(General)	Explosion-Proof	Other