

4318044

60175000
s53354b

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

June 6, 2012
13:38

C H R Y S L E R
HAZARD COMMUNICATION SHEET

94996
PREPARATION DATE: 11-22-11 STNDRD: N/AV PART/COMMTY CD: 04318044
OSHA HAZ: YES HAZWOPER HAZ: YES SUPPLIER: 59028 MFGR: 03500
CONS PROD/HAZ SUB: NO

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: MOPAR THREAD SEALANT
MFG ID : 592
DESCRIPTION: SEALANT-THREAD

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS:	PERCENT					
COMM NAME / CAS NO & CHEM NAME:	BY WGT	OSHA	ACGIH	CHRY S	UNITS	NOTATIONS
EXISTING INGREDIENTS						
N-OCTYL ALCOHOL	10-30	W	N/AP	N/AP	50	PPM
000111-87-5 1-OCTANOL (9CI)						
SILICA, MICA	10-30	W	3	3	3	MG/M3
012001-26-2 SILICATE, MICA						
TITANIUM DIOXIDE	1-5	W	10	10	10	MG/M3 I2B
013463-67-7 TITANIUM OXIDE (TIO2						
BISPHENOL A -FUMARATE RESIN	10-30	W	N/AV	N/AV	N/AV	N/AV
039382-25-7 2-BUTENEDIOIC ACID (
POLYETHYLENE GLYCOL DIMETHACRYLAT	10-30	W	N/AV	N/AV	N/AV	N/AV
025852-47-5 POLY(OXY-1,2-ETHANED						
TETRAETHYLENE GLYCOL DI-2-ETHYLHE	10-30	W	N/AV	N/AV	N/AV	N/AV
018268-70-7 HEXANOIC ACID, 2-ETH						
TEFLON	5-10	W	N/AP	N/AP	N/AP	N/AP
009002-84-0 ETHENE, TETRAFLURO-						
CUMENE HYDROPEROXIDE	1-5	W	N/AP	N/AP	N/AP	N/AP
000080-15-9 HYDROPEROXIDE, 1-MET						T

BALANCE:

HEXAMETHYLDISILAZANE, SILICA REACTION PRODUCT/
ODOR MASK (ESTER BASED)/

GENERIC DESC: MATERIAL CONSISTING OF THE FOLLOWING: RESIN(S), SILICA
CONTAINING COMPOUNDS, ALCOHOL(S), FILLER(S), ESTER(S) AND METAL
OXIDE(S).

Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : > 300 F SOLUB IN WATER: SLIGHT (0.1 - 1%)
VAPOR PRESSURE: < 10 MM HG AT 80 F EVAP. RATE: N/AV REF: N/AV
VAPOR DENSITY : N/AV SPECIFIC GRAVITY: 1.210 AT 80 F
PH AT FULL STRENGTH: N/AP PH AT REC. DILUT: N/AP
%VOLATILE BY VOL : < 17.0 VOLATILE ORGANIC COMP: 1.70655 LB/GAL
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV
APPEARANCE & ODOR: COLOR: WHITE..... STATE: PASTE..... ODOR: MILD.....

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

FLASH POINT: > 200 F TCC IGN TEMP: N/AV LEL: N/AV UEL: N/AV
SPECIAL FIRE & EXPLOSION HAZARDS:
WHEN HEATED TO DECOMPOSITION MAY PRODUCE TOXIC THERMAL DECOMPOSITION
PRODUCTS.
EXTINGUISHING MEDIA:
CARBON DIOXIDE, FOAM, DRY CHEMICAL.
SPECIAL FIREFIGHTING PROCEDURES:
USE PROTECTIVE CLOTHING. AVOID BREATHING VAPOR OR FUMES. USE SELF-CONTAINED
BREATHING APPARATUS. USE WATER TO COOL FIRE EXPOSED CONTAINERS. REMOVE
CONTAINERS FROM FIRE AREA IF POSSIBLE.
SENSITIVE TO MECHANICAL IMPACT?: NO SENSITIVE TO STATIC DISCHARGE?: NO
HAZARDOUS COMBUSTION PRODUCTS:
TOXIC FLUORIDES.
FLAME PROJECTION: N/AP

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:
<<---INHALATION--->> VAPOR-MAY BE IRRITATING TO EYES, NOSE, AND THROAT.
HIGH CONCENTRATION MAY PRODUCE THE FOLLOWING: ACUTE NERVOUS SYSTEM
DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING, CONFUSION,
UNCONSCIOUSNESS OR COMA. <<---SKIN CONTACT--->> DIRECT CONTACT MAY PRODUCE
THE FOLLOWING: MINOR IRRITATION. PROLONGED SKIN EXPOSURE MAY RESULT IN THE
FOLLOWING: DERMATITIS. <<---EYE CONTACT--->> DIRECT CONTACT MAY PRODUCE THE
FOLLOWING: IRRITATION AND TEARING. <<---INGESTION--->> MAY BE HARMFUL IF
SWALLOWED.

EMERGENCY FIRST AID PROCEDURES:

<<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. IF PULMONARY SYMPTOMS
DEVELOP, CONSULT A PHYSICIAN. <<---SKIN CONTACT--->> REMOVE CONTAMINATED
CLOTHING. WASH WITH SOAP AND WATER. IF CONDITION PERSISTS, CONSULT A
PHYSICIAN. <<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS
OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15
MINUTES. CONTACT A PHYSICIAN. <<---INGESTION--->> DO NOT INDUCE
VOMITING-CALL PHYSICIAN IMMEDIATELY. KEEP WARM AND QUIET.

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

*** SECTION 06 - REACTIVITY DATA ***

STABILITY: STABLE

CONDITIONS TO AVOID:

HIGH TEMPERATURE.

MATERIALS TO AVOID:

NONE KNOWN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

TOXIC FLUORIDES MAY BE RELEASED UPON THERMAL DECOMPOSITION.

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

ABSORB ON AN INERT MATERIAL. DISPOSE OF WASTE IN A CLOSED HALF-FILLED CONTAINER. DO NOT MIX WITH OTHER WASTE OR SUBSTANCES.

WASTE DISPOSAL METHODS:

INCINERATE. DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL DISPOSAL REGULATIONS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

WEAR THE FOLLOWING: ORGANIC VAPOR RESPIRATOR. THIS EQUIPMENT MAY BE NEEDED IF THE ALLOWABLE LIMIT OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED..

VENTILATION TYPE:

LOCAL EXHAUST VENTILATION.. THIS EQUIPMENT MAY BE NEEDED TO MAINTAIN THE TLV..

PROTECTIVE GLOVES:

RECOMMENDED. RUBBER GLOVES OR PLASTIC GLOVES.

EYE PROTECTION:

RECOMMENDED. SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

APRON (SAME MATERIAL AS GLOVES)..

*** SECTION 09 - SPECIAL PRECAUTIONS ***

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE IN A COOL, DRY PLACE. KEEP FROM HEAT, SPARK OR OPEN FLAMES. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING VAPOR. AVOID SKIN CONTACT. AVOID EYE CONTACT. AVOID INGESTION. WASH THOROUGHLY AFTER HANDLING. REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE REUSE. MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

60175000
s53354b

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

June 6, 2012
13:38

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP
NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

WASTE CODE(S)/HZD: | MICH: N/AP

THE ABOVE INFORMATION IS BASED ON DATA PROVIDED BY SUPPLIERS. TESTING IS NOT
NEEDED