MATERIAL SAFETY DATA SHEET



PRODUCT IDENTIFICATION

MANUFACTURER'S NAME AND ADDRESS:

PROSOCO, Inc.

37.41 Greenway Circle Lawrence, KS 66046

EMERGENCY TELEPHONE NUMBERS: 8:00 AM - 5:00 PM CST Monday-Friday: NON-BUSINESS HOURS (INFOTRAC):

785/865-4200 800/535-5053

PRODUCT TRADE NAME:

Consolideck[®] Saltguard[®] WB

HAZARDOUS INGREDIENTS

CHEMICAL NAME

(COMMON NAME)

CAS NO.

HMIS CODE

ACGIH TLV/TWA

OSHA PEL/TWA

Silane, triethoxyoctyl

(Proprietary)*

2943-75-1

1.2.0-

None established

None established

*Specific chemical identity withheld as trade secret pursuant to OSHA regulations.

Hydrolysis by-products are present in product as supplied in minute concentrations. These materials evolve slowly during curing.

III PHYSICAL DATA

BOILING POINT (°F) Silane, triethoxyoctyl 212

VAPOR PRESSURE (mm Hg) ND

VAPOR DENSITY (Air = 1)

EVAPORATION RATE (Butyl Acetate = 1)

approx. 1

ND

Consolideck® Saltquard® WB

SPECIFIC **GRAVITY** 0.997

SOLUBILITY IN WATER

100%

APPEARANCE AND ODOR

White liquid, odorless

FIRE AND EXPLOSION HAZARD DATA

EMERGENCY OVERVIEW

Consolideck Saltguard WB is a white, odorless, liquid. Contact with the eyes or skin may result in irritation. Always wear appropriate personal protective equipment when using this product.

FLASH POINT (METHOD): > 212°F (ASTM D 3278)

FLAMMABLE LIMITS: Not applicable.

EXTINGUISHING MEDIA: Foam, carbon dioxide, water spray.

SPECIAL FIRE FIGHTING PROCEDURES: None.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Although there is no flash point, flammable vapors may accumulate in the headspace of the container when storage times of six months are exceeded.

V HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE: Skin and eyes.

CARCINOGEN INFORMATION: Not listed (OSHA, IARC, NTP).

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: No applicable information found.

EFFECTS OF OVEREXPOSURE: Eye and skin irritation possible with direct contact.

EYE CONTACT: Causes eye irritation.

SKIN CONTACT: Causese skin irritation.

INHALATION: No harmful effects have been reported upon inhalation.

INGESTION: No harmful effects reported.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: If in eyes, flush with large amounts of water for 15 minutes, holding eyelids apart to ensure flushing of the entire eye

surface. Get medical attention.

SKIN CONTACT: Wash exposed area with soap and water. Remove contaminated clothing. If persistent irritation occurs, get medical

attention. Launder contaminated clothing before reuse.

INHALATION: No respiratory effects have been reported.

INGESTION: Seek medical assistance.

VI REACTIVITY DATA

STABILITY: Relatively non-reactive, but will hydrolyze slowly at ambient temperatures to form alcohol.

CONDITIONS TO AVOID: Heat, frost.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, oxidants, alkalis.

HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: After long periods of time, small amounts of alcohol may be

formed in the container headspace.

VII SPILL OR LEAK PROCEDURES

SPILL, LEAK, WASTE DISPOSAL PROCEDURES: Wear appropriate protective safety equipment. Control spill with absorbent pads or brooms. If necessary, apply granular or loose sorbent to spill. When absorbed, sweep or otherwise collect and dispose of properly. Floors may be slippery; care should be exercised to avoid falls.

WASTE DISPOSAL METHODS: Dispose of in a manner approved for this material. As of this writing, the product is not classified as a hazardous waste, however, federal regulation prohibits disposal of liquid materials of any kind in a sanitary landfill. Solidify cleanup residuals before disposal. As local and state regulations may vary, consult with appropriate state and local regulatory agencies or the sanitary landfill operator to ascertain proper disposal procedures.

Empty containers must not be reused. Drain all liquid possible from the container before disposal in a sanitary landfill.

VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear a NIOSH approved dust/mist respirator as necessary to avoid unnecessary inhalation of wind drift during application.

VENTILATION: Mechanical local exhaust at point of use.

PROTECTIVE CLOTHING: Wear protective clothing such as long sleeved work shirt and pants, work boots, and rubber gloves as needed to avoid skin contact. Do not allow clothing to become saturated with product. If work practices cannot be adjusted to avoid excess clothing saturation, splash resistant or Tyvek clothing and boots may be required.

PROTECTIVE GLOVES: Chemically resistant gloves such as nitrile, rubber, or PVC may be used.

EYE PROTECTION: Safety glasses with side shields are recommended. Splash resistant goggles or a face shield should be used prevent eye contact where wind-drift and excess atomization can pose a risk

OTHER PROTECTIVE EQUIPMENT: Access to an eyewash is recommended. Personal protective clothing and use of equipment must be in accordance with 29 CFR 1910.133 and 29 CFR 19120. 132.

IX SPECIAL PRECAUTIONS

WORK PRACTICES: Proper work practices and planning should be utilized to avoid contact with workers, passersby, and non-masonry surfaces. Do not atomize during application. Beware of wind drift. See the Product Data sheet and label for specific precautions to be taken during use. Wash hands before breaks and at the end of a shift.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Wear appropriate safety equipment and clothing. Do not get in eyes, on skin, or on clothing. Do not take internally. Avoid breathing mist. Never touch face with hands or gloves that may be contaminated with this product.

Store in a cool, dry, well-ventilated place. Keep containers tightly closed when not dispensing product. Use care around spilled material because it will be slippery.

OTHER PRECAUTIONS: None known.

X REGULATORY INFORMATION

SHIPPING: This product is not regulated for domestic or international shipment.

SARA 313 REPORTABLE:

CHEMICAL NAME CAS UPPERBOUND CONCENTRATION % BY WEIGHT

NA NA NA

CALIFORNIA PROPOSITION 65: This product contains no chemicals listed under California's Proposition 65.

XI OTHER

MSDS Status:

Date of Revision: July 19, 2007

For Product Manufactured After: August 1, 2007 Changes: Updated Product Item #, Section XI

Item #: 46067

Approved By: Regulatory Department

DISCLAIMER:

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

DATE OF PREPARATION: August 1, 2007