


**Material Safety Data Sheet**   
**Genetron HP81 (R-402B)**  
Version 2 Revision Date 10/25/2007 Print Date 10/25/2007

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : **Genetron HP81 (R-402B)**  
MSDS Number : 000000011263  
Product Use Description : Refrigerant

Company : Honeywell International, Inc.  
101 Columbia Road  
Morristown, NJ 07962-1057

For more information call : 800-522-8001  
(Monday-Friday, 9:00am-5:00pm)

**In case of emergency call : Medical: 1-800-498-5701**  
**Transportation: 1-800-424-9300 or 703-527-3887**  
(24 hours/day, 7 days/week)

**SECTION 2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : slight sweet ether-like

Hazard Summary : Warning! Container under pressure. This product is not flammable at ambient temperatures and atmospheric pressure. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. Irritating to eyes and skin. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250°C), decomposition products may include hydrochloric acid (HCl), hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

**Potential Health Effects**

Skin : Avoid skin contact with leaking liquid (danger of frostbite).  
May cause frostbite.  
Irritating to skin.

Eyes : Causes severe eye irritation.  
May cause frostbite.

Ingestion : Unlikely route of exposure.

Material Safety Data Sheet		Honeywell
Genetron HP81 (R-402B)		
Version 2	Revision Date 10/25/2007	Print Date 10/25/2007
Inhalation	: Effects due to ingestion may include: Gastrointestinal discomfort	
	: Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. Vapours may cause drowsiness and dizziness.	
Chronic Exposure	: None known.	
<b>Carcinogenicity</b>		
No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.		
<b>SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS</b>		
Component	CAS-No.	Weight %
Chlorodifluoromethane	75-45-6	60.00
Pentafluoroethane	354-33-6	38.00
Propane	74-98-6	2.00
<b>SECTION 4. FIRST AID MEASURES</b>		
<b>Inhalation</b>	: Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.	
<b>Skin contact</b>	: After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.	
<b>Eye contact</b>	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.	
<b>Ingestion</b>	: Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.	
<b>Notes to physician</b>		
<b>Treatment</b>	: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support.	
2 / 10		

Material Safety Data Sheet		Honeywell
Genetron HP81 (R-402B)		
Version 2	Revision Date 10/25/2007	Print Date 10/25/2007
Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.		
<b>SECTION 5. FIRE-FIGHTING MEASURES</b>		
Flash point	:	not applicable
Lower explosion limit	:	None
Upper explosion limit	:	None
Suitable extinguishing media	:	The product is not flammable. ASHRAE 34 Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment
Specific hazards during fire fighting	:	Contents under pressure. This product is not flammable at ambient temperatures and atmospheric pressure. However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources. Container may rupture on heating. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. In case of fire hazardous decomposition products may be produced such as: Gaseous hydrogen chloride (HCl). Hydrogen fluoride Carbon monoxide Carbon dioxide (CO <sub>2</sub> ) Carbonyl halides
Special protective equipment for fire-fighters	:	In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit. No unprotected exposed skin areas.
<b>SECTION 6. ACCIDENTAL RELEASE MEASURES</b>		
Personal precautions	:	Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Wear personal protective equipment. Unprotected persons must be kept away. Remove all sources of ignition. Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area.
3 / 10		

<b>Material Safety Data Sheet</b>	<b>Honeywell</b>
<b>Genetron HP81 (R-402B)</b>	
Version 2	Revision Date 10/25/2007
Print Date 10/25/2007	

After release, disperses into the air.  
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
 Avoid accumulation of vapours in low areas.  
 Unprotected personnel should not return until air has been tested and determined safe.  
 Ensure that the oxygen content is  $\geq 19.5\%$ .

Environmental precautions : Prevent further leakage or spillage if safe to do so.  
 The product evaporates readily.

Methods for cleaning up : Ventilate the area.

**SECTION 7. HANDLING AND STORAGE**

**Handling**

Handling : Handle with care.  
 Avoid inhalation of vapour or mist.  
 Do not get in eyes, on skin, or on clothing.  
 Wear personal protective equipment.  
 Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.  
 Follow all standard safety precautions for handling and use of compressed gas cylinders.  
 Use authorized cylinders only.  
 Protect cylinders from physical damage.  
 Do not puncture or drop cylinders, expose them to open flame or excessive heat.  
 Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.  
 Do not remove screw cap until immediately ready for use.  
 Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.  
 Can form a combustible mixture with air at pressures above atmospheric pressure.

**Storage**

Requirements for storage areas and containers : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
 Keep containers tightly closed in a dry, cool and well-ventilated place.  
 Storage rooms must be properly ventilated.  
 Ensure adequate ventilation, especially in confined areas.  
 Protect cylinders from physical damage.

**SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Material Safety Data Sheet** **Honeywell**  
**Genetron HP81 (R-402B)**  
 Version 2 Revision Date 10/25/2007 Print Date 10/25/2007

- Protective measures : Do not breathe vapour.  
 Avoid contact with skin, eyes and clothing.  
 Ensure that eyewash stations and safety showers are close to the workstation location.
  
- Engineering measures : General room ventilation is adequate for storage and handling.  
 Perform filling operations only at stations with exhaust ventilation facilities.
  
- Eye protection : Wear as appropriate:  
 Safety glasses with side-shields  
 If splashes are likely to occur, wear:  
 Goggles or face shield, giving complete protection to eyes
  
- Hand protection : Leather gloves  
 In case of contact through splashing:  
 Protective gloves  
 Neoprene gloves  
 Polyvinyl alcohol or nitrile- butyl-rubber gloves
  
- Skin and body protection : Protective suit  
 Avoid skin contact with leaking liquid (danger of frostbite).  
 Wear cold insulating gloves/face shield/eye protection.
  
- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.  
 Wear a positive-pressure supplied-air respirator.  
 Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
 For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
  
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
 Ensure adequate ventilation, especially in confined areas.  
 Avoid contact with skin, eyes and clothing.  
 Remove and wash contaminated clothing before re-use.  
 Keep working clothes separately.

**Exposure Guidelines**

Chlorodifluoromethane	75-45-6	ACGIH	TWA		1,000 ppm
		NIOSH	REL	1,000 ppm	3,500 mg/m3
		NIOSH	STEL	1,250 ppm	4,375 mg/m3
		US CA OEL	TWA PEL	1,000 ppm	3,500 mg/m3
		OSHA Z1A	TWA	1,000 ppm	3,500 mg/m3
Pentafluoroethane	354-33-6	WEEL	TWA	1,000 ppm	4,900 mg/m3
Propane	74-98-6	NIOSH	REL	1,000 ppm	1,800 mg/m3

**Material Safety Data Sheet** **Honeywell**

**Genetron HP81 (R-402B)**

Version 2 Revision Date 10/25/2007 Print Date 10/25/2007

OSHA Z1	PEL	1,000 ppm	1,800 mg/m3
OSHA Z1A	TWA	1,000 ppm	1,800 mg/m3
US CA OEL	TWA PEL	1,000 ppm	1,800 mg/m3
ACGIH	TWA		1,000 ppm

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquefied gas
- Color : colourless
- Odor : slight sweet ether-like
- Molecular Weight : 94.7 g/mol
- pH : neutral
- : not determined
- Boiling point/boiling range : -47.4 °C (-53.3 °F)
- Vapor pressure : 10,052 hPa  
at 21.1 °C (70.0 °F)
- Vapor pressure : 22,635 hPa  
at 54.4 °C (129.9 °F)
- Relative vapour density : 3.3  
(Air = 1.0)
- Density : 1.14 g/cm3  
at 21.1 °C (70.0 °F)
- Water solubility : not determined

**SECTION 10. STABILITY AND REACTIVITY**

- Conditions to avoid : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.  
Decomposes under high temperature.  
Some risk may be expected of corrosive and toxic decomposition products.  
Can form a combustible mixture with air at pressures above atmospheric pressure.  
Do not mix with oxygen or air above atmospheric pressure.
- Materials to avoid : Finely divided aluminium  
Potassium  
Calcium

Material Safety Data Sheet		Honeywell
Genetron HP81 (R-402B)		
Version 2	Revision Date 10/25/2007	Print Date 10/25/2007
	Powdered metals Aluminium Magnesium Zinc	
Hazardous decomposition products	:	In case of fire hazardous decomposition products may be produced such as: Gaseous hydrogen chloride (HCl). Hydrogen fluoride Carbonyl halides Carbon monoxide Carbon dioxide (CO <sub>2</sub> )
Thermal decomposition	:	>250 °C
Hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
<b>SECTION 11. TOXICOLOGICAL INFORMATION</b>		
Acute inhalation toxicity (Component)		Component: 75-45-6 Chlorodifluoromethane rat Exposure time: 4 h
Acute inhalation toxicity (Component)		Component: 354-33-6 Pentafluoroethane rat Exposure time: 4 h
Additional advice	:	Acute Health Hazard Chlorodifluoromethane (HCFC-22): Cardiac sensitisation threshold (dog): 50000 ppm. Ethane, pentafluoro- (HFC-125): Cardiac sensitisation threshold (dog): 75000 ppm. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Irritating to eyes and skin. Rapid evaporation of the liquid may cause frostbite. May cause cardiac arrhythmia.
<b>SECTION 12. ECOLOGICAL INFORMATION</b>		
Additional ecological information	:	This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered. This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82. Section 611 requires the following label text on all shipments of this product: Warning: Contains Chlorodifluoromethane (HCFC-22),
7/10		

<b>Material Safety Data Sheet</b>		<b>Honeywell</b>
<b>Genetron HP81 (R-402B)</b>		
Version 2	Revision Date 10/25/2007	Print Date 10/25/2007
<p>a substance which harms public health and environment by destroying ozone in the upper atmosphere.                  Refer to sections 610 and 612 for list of acceptable and unacceptable uses for this product.</p>		
<b>SECTION 13. DISPOSAL CONSIDERATIONS</b>		
<p>Waste Information: Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of according to all federal, state and local applicable regulations.</p> <p>Other Disposal Considerations: Observe all Federal, State, and Local Environmental regulations.</p> <p>The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.</p> <p>Additional advice : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.</p>		
<b>SECTION 14. TRANSPORT INFORMATION</b>		
<b>DOT</b>	Proper shipping name	: LIQUEFIED GAS, N.O.S.
	UN-Number	: 3163
	Class	: 2.2
	Packing group	:
<b>IATA</b>	UN Number	: 3163
	Description of the goods	: LIQUEFIED GAS, N.O.S.
	Class	: 2.2
	Hazard Label	: 2.2
	Packing instruction (cargo aircraft)	: 200
	Packing instruction (passenger aircraft)	: 200
<b>IMDG</b>	Substance No.	: UN 3163
	Description of the goods	: LIQUEFIED GAS, N.O.S.
	Class	: 2.2
	Hazard Label	: 2.2
	EmS Number	: F-C
	Marine pollutant	: no
<b>SECTION 15. REGULATORY INFORMATION</b>		
<b>Inventories</b>		
8 / 10		



Material Safety Data Sheet		Honeywell
Genetron HP81 (R-402B)		
Version 2	Revision Date 10/25/2007	Print Date 10/25/2007
EU. EINECS	: On or in compliance with the inventory	
US. Toxic Substances Control Act	: On TSCA Inventory	
Australia. AICS	: On or in compliance with the inventory	
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	: All components of this product are on the Canadian DSL list.	
Japan. ENCS	: On or in compliance with the inventory	
Korea. KECI	: On or in compliance with the inventory	
Philippines. PICCS	: On or in compliance with the inventory	
China. IECSC	: On or in compliance with the inventory	
<b>National regulatory information</b>		
<b>SARA 313 Components</b>	: Chlorodifluoromethane	75-45-6
<b>SARA 311/312 Hazards</b>	: Acute Health Hazard Sudden Release of Pressure Hazard	
<b>California Prop. 65</b>	: This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.	
<b>Massachusetts RTK</b>	: Chlorodifluoromethane	75-45-6
	: Propane	74-98-6
<b>New Jersey RTK</b>	: Chlorodifluoromethane	75-45-6
	: Pentafluoroethane	354-33-6
	: Propane	74-98-6
<b>Pennsylvania RTK</b>	: Chlorodifluoromethane	75-45-6
	: Pentafluoroethane	354-33-6
	: Propane	74-98-6
<b>WHMIS Classification</b>	: A	

**Material Safety Data Sheet** **Honeywell**  
**Genetron HP81 (R-402B)**  
Version 2 Revision Date 10/25/2007 Print Date 10/25/2007

**SECTION 16. OTHER INFORMATION**

	<b>HMIS III</b>	<b>NFPA</b>
Health Hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0