

4874000

Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP

C H R Y S L E R
HAZARD COMMUNICATION SHEET

2005025 DRAFT PART/COMMTY CD: 05013781AA
PREPARATION DATE: 01-02-03 STNDRD: MS-9469 SUPPLIER: 68364 MFGR: 03500
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: MOPAR GREASE (MS-9469)
MFG ID : 760G
DESCRIPTION: GREASE-DIELECTRIC

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS: PERCENT
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS
EXISTING INGREDIENTS
SILANE, DICHLORODIMETHYL-, REACTI 10-30 W N/AV N/AV N/AV N/AV
068611-44-9 SILANE, DICHLORODIME
BALANCE:
DECENE, OCTENE POLYMER, HYDROGENATED/
GENERIC DESC: STATE: GREASE..... CONTAINING THE FOLLOWING: POLYMER(S), SILICA
CONTAINING COMPOUNDS, AMINE(S), ORGANIC ACID(S) AND ALIPHATIC
HYDROCARBON(S).

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : N/AV SOLUB IN WATER: NEGLIGIBLE (< 0.1%)
VAPOR PRESSURE: N/AP EVAP. RATE: < 1.000 REF: ETHYL ETHER
VAPOR DENSITY : > 1.000 AT N/AV SPECIFIC GRAVITY: 0.910 AT N/AV
PH AT FULL STRENGTH: 7.0 PH AT REC. DILUT: N/AV
%VOLATILE BY VOL : 0.0 VOLATILE ORGANIC COMP: N/AP N/AP
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV
APPEARANCE & ODOR: APPEARANCE: SMOOTH..... APPEARANCE: TRANSLUCENT..... COLOR:
OFF-WHITE..... ODOR: ODORLESS..... STATE: GREASE.....

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

FLASH POINT: > 400 F COC IGN TEMP: N/AV LEL: N/AV UEL: N/AV

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

SPECIAL FIRE & EXPLOSION HAZARDS:

MAY PRODUCE TOXIC THERMAL DECOMPOSITION PRODUCTS.

EXTINGUISHING MEDIA:

CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER.

SPECIAL FIREFIGHTING PROCEDURES:

USE PROTECTIVE CLOTHING. AVOID BREATHING VAPOR OR FUMES. USE SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE. WATER OR FOAM MAY CAUSE FROTHING.

SENSITIVE TO MECHANICAL IMPACT?: NO SENSITIVE TO STATIC DISCHARGE?: NO

HAZARDOUS COMBUSTION PRODUCTS:

TOXIC FUMES OR VAPORS, CARBON MONOXIDE AND CARBON DIOXIDE.

FLAME PROJECTION: N/AP

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---INHALATION--->> IF HEATED-ACUTE EXPOSURE MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT AND MAY BE IRRITATING TO EYES, NOSE, AND THROAT. <<---SKIN CONTACT--->> PROLONGED SKIN EXPOSURE MAY RESULT IN THE FOLLOWING: IRRITATION. <<---EYE CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: IRRITATION AND TEARING. <<---INGESTION--->> NO KNOWN EFFECTS. HOWEVER, INGESTION IS NOT RECOMMENDED.

EMERGENCY FIRST AID PROCEDURES:

<<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. CONTACT A PHYSICIAN.
<<---SKIN CONTACT--->> WASH WITH SOAP AND WATER. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. IF CONDITION PERSISTS, CONSULT A PHYSICIAN.
<<---INGESTION--->> DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY. DRINK LARGE QUANTITIES OF WATER.

*** SECTION 06 - REACTIVITY DATA ***

STABILITY: STABLE

CONDITIONS TO AVOID:

HIGH TEMPERATURE AND RUN-OFF TO SEWER SYSTEMS.

MATERIALS TO AVOID:

STRONG OXIDIZING AGENTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

TOXIC FUMES OR VAPORS, CARBON MONOXIDE AND CARBON DIOXIDE.

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

SPILLS ARE VERY SLIPPERY. WIPE UP OR SCRAPE UP SMALL SPILL OR RESIDUE.
LARGE SPILL-USE OIL ABSORPTION COMPOUND OR ABSORB WITH DIATOMACIOUS EARTH.
SHOVEL INTO STORAGE CONTAINERS. RESIDUE-WASH AREA WITH DETERGENT AND WATER.
DO NOT FLUSH INTO SEWER SYSTEM.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND
FEDERAL DISPOSAL REGULATIONS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. IF THE PRODUCT IS
MISTED, USE THE FOLLOWING: OR IF THE PRODUCT IS HEATED TO DECOMPOSITION, USE
THE FOLLOWING: DUST AND MIST RESPIRATOR OR AIR-SUPPLIED RESPIRATOR.

VENTILATION TYPE:

THE FOLLOWING IS USUALLY ADEQUATE: GENERAL VENTILATION. TO MAINTAIN THE
TLV, THE FOLLOWING MAY BE NEEDED: LOCAL EXHAUST VENTILATION.

PROTECTIVE GLOVES:

TO AVOID PROLONGED SKIN CONTACT, USE THE FOLLOWING: OIL RESISTANT
GLOVES-NEOPRENE GLOVES, NITRILE RUBBER GLOVES OR BUTYL RUBBER GLOVES.

EYE PROTECTION:

RECOMMENDED. SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

TO AVOID PROLONGED SKIN CONTACT, USE THE FOLLOWING: APRON (SAME MATERIAL AS
GLOVES). PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING. WASH
CONTAMINATED CLOTHING BEFORE REUSE. A SAFETY SHOWER MAY BE NEEDED FOR
EMERGENCY SITUATIONS. AN EYE WASH MAY BE NEEDED FOR EMERGENCY SITUATIONS.

*** SECTION 09 - SPECIAL PRECAUTIONS ***

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE IN A COOL, DRY PLACE. STORE SEPARATE FROM INCOMPATIBLE MATERIALS.
REACTS WITH OXIDIZERS. PRODUCT TENDS TO MAKE SURFACES, SUCH AS FLOORS,
SLIPPERY. DO NOT SMOKE OR EAT WHEN HANDLING THIS SUBSTANCE; WASH THOROUGHLY
AFTER USING. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. DO NOT STORE IN
OPEN OR UNLABELED CONTAINERS.

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING MIST. AVOID EYE CONTACT. AVOID PROLONGED OR REPEATED SKIN
CONTACT. AVOID INGESTION. WASH THOROUGHLY AFTER HANDLING. REMOVE
CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. MAINTAIN GOOD HOUSEKEEPING
AND HYGIENIC PRACTICES.

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP
NOT HAZARDOUS PER DOT REGULATIONS

60175000
s53354b

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

May 30, 2012
16:31

RCRA INFORMATION (40 CFR 122-124, 260-265)
INFORMATION UNAVAILABLE AT THIS TIME