# OSHA HAZARD COMMUNICATION STANDARD HAZARDOUS FINISHED GOODS 30-40 VOLUME DEVELOPER PRODUCTS

MSDS #99-029

REDKEN COLOR FUSION DOUBLE BLONDE 40 VOLUME DEVELOPER REDKEN LIFT 515 DEVELOPER 40 VOLUME REDKEN LIFT HIGHLIFTING 515 DEVELOPER 40 VOLUME

REDKEN PRO-OXIDE EMULSIFIED DEVELOPER 30 VOLUME REDKEN PRO-OXIDE EMULSIFIED DEVELOPER 40 VOLUME REDKEN SHADES EQ LIGHTENING SOLUTION

# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements

U.S. Department of Labor

#99-029

Occupation Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

# Section

IDENTITY

30-40 Volume Developer Products

Section	
Manufacturer's Name	Emergency Telephone Number
L'Oreal USA Products, Inc.	(732) 499-2990
Address (Number, Street, City, State, and ZIP Code)	Telephone Number For Information
2400 U.S. Route 1 North	(732) 940-4612
	Date Prepared
North Brunswick, NJ 08902	June 26, 2000
	Signature of Preparer (optional)
	lago

Section II - Hazardous Ingredients/Identity Information

		ACGIH	Other Limits	
Hazardous Components (Specific Chemical Identity;Common Name(s))	OSHA PEL	TLV	Recommended	% (optional)

Hydrogen Peroxide

1 ppm

9-12%

Section III - Physical/Chemical Characteristics

Boiling Point		Specific Gravity (H2O = 1)	
	~212°F		~1
Vapor Pressure (mm Hg)		Melting Point	
	N/A		N/A
Vapor Density (AIR = 1)		Evaporation Rate	
•	N/A	(Butyl Acetate = 1)	<1

Solubility in Water

Miscible

pH = ~2.5

Appearance and Odor

White, creamy, thick liquid with a faint odor.

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
>200°F (closed cup)	None	N/A:	N/A

Extinguishing Media

Use media appropriate for materials actually involved in the fire.

Special Fire Fighting Procedures

Upon decomposition, peroxides yield oxygen and may thereby stimulate the combustion of flammable and combustible materials. Extinguish fires with media appropriate for the burning material.

Unusual Fire and Explosion Hazards

Caution: Oxidizer. Residual product on towels, sponges, or mops may cause fire. Rinse towels thoroughly before disposal. Rinse sponges and mops thoroughly before storage.

Section V - Re	eactivity Data				#99-029	
Stability Unst	Unstable		Conditions to Avoid	Avoid contact with iron reducing agents.	, zinc, and	
	Stable	Х		_		
Incompatibility (Ma	iterials to Avoid)					
Organic com	pounds (incl	luding f	flammables an	d combustibles), iron, zim	nc, and reducing	
agents.						
Hazardous Decom	position or Byprodu	icts				
	beginen at alleran					
None known.		.4.5				
			Conditions to Avoid			
None known.		X		None known.		
None known. Hazardous Polymerization	May Occur	X		None known.		
None known. Hazardous Polymerization	May Occur Will Not Occur ealth Hazard D	X	Avoid	None known. Skin?	Ingestion?	

May cause skin and severe eye irritation. Harmful if swallowed. May cause severe irritation of gastric mucous membranes if swallowed.

Carcinogenicity: NTP? LARC Monographs? OSHA Regulated?
No No No No

Signs and Symptoms of Exposure

Irritation of skin, eyes, and/or mucous membranes.

Medical Conditions Generally Aggravated by Exposure

None known.

#### **Emergency and First Aid Procedure**

If swallowed, drink one or two glasses of water or milk. Call a physician, hospital emergency room, or poison control center immediately. Do not induce vomiting. Get medical attention. If in eyes, flush with water for at least 15 minutes and get medical attention. If on skin, flush with water, then wash with soap and plenty of water. Consult a physician if irritation occurs.

#### Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

For small spills, wipe up with paper towels or a sponge. Wash area with water. Rinse paper towels, sponges, or mops thoroughly prior to disposal or storage. For large spills, dike and contain the free liquid. Use absorbant material to solidify spill and then place in UN specification drums for disposal.

#### Waste Disposal Method

30-40 volume developer products are ignitable (D001) RCRA hazardous wastes when intended for disposal. Physical and/or chemical deactivation/degredation is the required method of treatment and disposal.

#### Precautions to be Taken in Handling and Storage

Do not use or store with near fuels, solvents, or other organic materials. Avoid iron, zinc, and reducing agents. Store in a cool place away from direct sunlight. Keep out of reach of children.

### Other Precautions

For external use only. Use only as directed.

#### Section VIII - Control Measures

#99-029

Respiratory Protection (Specify Type)

None required for product use. For handling bulk quantities, use NIOSH-approved respirator if peroxide TLV is exceeded. For spills or fires, wear a self-contained breathing apparatus.

Dreathing a	pparacus.			
Ventilation	Local Exhaust	Recommended	Special	
	Mechanical(General)	Acceptable	Other	

#### Protective Gloves

Plastic or rubber.

#### Other Protective Clothing or Equipment

Safety glasses with side shields (or full face shield) and protective clothing are recommended for manufacturing operations. Safety shower and eyewash station should be immediately available.

#### Work/Hygienic Practices

OSHA hazard classification: Oxidizer, irritant, slightly toxic.

DOT classification: Bulk - Hydrogen Peroxide, aqueous solution 5.1 UN 2984 PGIII

Finished Product - Consumer Commodity, ORM-D.

Forms published by ChemSW (707)864-0845