# **Material Safety Data Sheet**

Acrylic Undercoater-Sealer

# 1. Product and company identification

Phone: 262-538-1122

Product name Code Material uses Manufacturer

**Emergency overview** 

#### Acrylic Undercoater-Sealer 272SS Acrylic emulsion sealer Essential Industries, Inc. P.O. Box 12 Merton, WI 53056-0012

In case of emergency Validation date Print date Responsible name 1-800-843-6174 10/11/2011. 10/11/2011. Regulatory Affairs Department

#### Hazardous Material Information System (U.S.A.)

relational protection	-
Personal protection	B 0 = Insignificant
PERSONAL PROPERTY AND A STREET AND A ST	1 = Slight
Discrete and the second s	a 2 = Moderate
r ien oneonicy	3 = High
Flammahility	4 = Extreme
	RATING
Sealth .	1 HAZARD

# 2. Hazards identification

CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. Contains material that may cause target organ damage, based on animal data.

	Contains material that may cause target organ
Potential acute health eff	fects due to overexposure
Inhalation	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.
Skin	No known significant effects or critical hazards.
Eyes	No known significant effects or critical hazards.
Potential chronic health	effects due to overexposure
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
See toxicological information	ation (section 8)

# 3. Composition/information on ingredients

Name	CAS number	<u>%</u>
diethylene glycol monoethyl ether	111-90-0	1-5
ethanediol	107-21-1	1 - 5
SARA 313 (Form R - Reporting requirements)		
Product name	CAS number	Concentration
diethylene glycol monoethyl ether	111-90-0	3.4
ethanediol	107-21-1	1.7408
SARA 313 notifications must not be detached from the MSDS and any conving an	d redistribution of t	the MSDS shall include conving and redistribution

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

# 4. First aid measures

Eye contact	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation	Move exposed person to fresh air. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention immediately.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
Notes to physician	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

### 5. Fire-fighting measures

Flammability of the product	In a fire or if heated, a pressure increase will occur and the container may burst.
Extinguishing media	
Suitable	Use an extinguishing agent suitable for the surrounding fire.
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous thermal decompositio products	n Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### 6. Control and preventive measures

Storage Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Ingredient Exposure limits		Exposure limits		
diethylene glycol monoethyl ether ethanediol		AIHA WEEL (United States, 1/2009). TWA: 25 ppm 8 hour(s). OSHA PEL 1989 (United States, 3/1989). CEIL: 50 ppm CEIL: 125 mg/m <sup>3</sup>		
Personal protect Respiratory		ate ventilation is good industrial practice.		
Hands		complying with an approved standard should be worn at all times when		

	······································
Skin	Personal protective equipment for the body should be selected based on the task being performed and the
	risks involved and should be approved by a specialist before handling this product.

S	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is
	necessary to avoid exposure to liquid splashes, mists or dusts.

Methods for cleaning up

Eyes

Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Waste disposal	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

# 7. Physical and chemical properties

Physical state	Liquid	Boiling/condensation point	100°C (212°F)	
Color	Milky White	Melting/freezing point	0°C (32°F)	
Odor	Bland	Vapor pressure	<4 kPa (<30 mm Hg)	
VOC *	0.56 g/L	Vapor density	<1 [Air = 1]	
pН	9.2 to 9.6	Weight per Gallon:	8,49 lbs./gal.	
1% pH:	Not available	Specific Gravity:	1.02 gm/ml	
1 Title 47. Collinguite Code of De	autotions, Division 2, Oberster 1, Dubebaster 0, C.	Adiala O. Casasumas Description Continue 04500		

\* Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

### 8. Toxicological information

Acute toxicity Product/ingredient name ethanediol diethylene glycol monoethyl eth Conclusion/Summary		Result LD50 Oral LD50 Oral	Species Rat Rat	Dose 4700 mg/kg 7500 mg/kg	Exposure - -	
Chronic toxicity Conclusion/Summary	Not available					
9. Transport in	nformation					

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated	-	-	-		-

PG\* : Packing group