MATERIAL SAFETY DATA SHEET

Warren Unilube, Inc.

Address:

915 E. Jefferson Ave.

West Memphis, AR 72301

Phone:

(800) 428-9284

CHEMTREC NUMBER Domestic: 800-424-9300 International: 703-527-3887

PRODUCT IDENTIFICATION

Trade Name: Advance Multi-Vehicle ATF

Date Revised: June 24, 2008

Synonyms/product Code: N.A.

Chemical Name:

Petroleum Mineral Oil

Family Description:

A complex combination of hydrocarbons from a petroleum fraction obtained by

solvent crystallization plus additives.

DOT Hazard Class:

Not Applicable

COMPOSITION

Occupational Exposure Limits*

| Product | CAS Number | <u>Wt%</u> | OSHA <u>PEL</u> | ACGI <u>TLV</u> | H <u>Other</u> | <u>Units</u> |
|---|------------|------------|--------------------|--------------------|-------------------|--------------|
| Advance Multi-Vehicle ATF | Mixture | 100 | N.A. | N.A. | | |
| Ingredient(s): Solvent Dewaxed | 64742-65-0 | 85 | 5 | 5 | 10 STEL | mg/m³** |
| Heavy Paraffinic Additives Containing Acid Esters | N.A. | <15 | N.A. | N.A. | N.A. | N.A. |

^{* = 8-}Hr. TWA unless otherwise specified.

^{** =} As mineral oil Mist

^{*** =} All ingredients in this product are listed in the T.S.C.A. Inventory.

N.A. = Not Available

STEL = Short Term Exposure Limit; 15 minutes.

Advance Multi-Vehicle ATF Page 2 of 4

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point 760 mmHg: N.A. Pour Point: -40F

Vapor Pressure mmHg @ 100F: N.A. Vapor Density (air=1): N.A. Solubility in H₂O %: N.A. Nil. pH: Specific Gravity (H2O): Evaporation Rate (ethyl ether =1): N.A. 0.8762 % Volatile by Volume: N.A. Odor: Slight hydrocarbon odor

Viscosity (method, temp): 7.10 cst,100C Appearance: Red Liquid

N.A. = Not Available

FIRE AND EXPLOSION DATA

Flash Point: 415F COC

Flammable Limits in Air % by Vol. Lower: N.A. Upper: N.A.

Autoignition Temperature:

Extinguishing Media: Dry chemical, foam, carbon dioxide or water spray.

Special Fire Fighting Procedure: Water spray may be ineffective on flames but should be used to keep fire-

exposed containers cool. Firefighters should wear self-contained breathing

apparatus.

Unusual Fire or Explosion Hazard: May ignite when sufficient heat is applied.

REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will not occur.

Conditions to Avoid/Incompatibility: Strong oxidizing agents, heat, spark, flame and build-up of static electricity.

Hydrogen sulfide, carbon monoxide, carbon dioxide, aldehydes, ketones, and

Hazardous Decomposition Products: Hydrogen sulfide, carbon monoxide, carbon dioxide, aldehyd combustion products of sulfur and nitrogen.

HEALTH HAZARD DATA

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No IARC Monographs: No OSHA Regulated: No

Occupational Exposure Limits: See <u>COMPOSITION</u> section.

Effects of Overexposure:

Acute: Eyes:

The heavy paraffinic petroleum distillate fraction of this product is believed

be minimally irritating.

Advance Multi-Vehicle ATF Page 3 of 4

Skin: The heavy paraffinic petroleum distillate fraction of this product is believed to be

minimally irritating.

Inhalation: The inhalation hazards of this products components are negligible to minimally

irritating if airborne concentrations are kept below permissible occupational

exposure limits.

Ingestion: Ingestion hazards range from practically non-toxic to minimally toxic for the

components of this product. If vomiting occurs, product is an aspiration hazard.

<u>Chronic</u>: Frequent or prolonged contact may cause skin irritation.

Additional Medical and Toxicological Information:

May aggravate pre-existing dermatitis. The International Agency for Research on

Cancer (IARC) has determined that there is sufficient evidence for the

carcinogenicity in experimental animals of used oil.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush thoroughly with water for at least 15 minutes. Get medical attention.

Skin Contact: Remove contaminated clothing. Wash affected areas with soap and water. If

irritation occurs, get medical help.

Inhalation: Remove to fresh air, Apply artificial respiration if not breathing. Get medical

attention.

Ingestion: Do not induce vomiting. If spontaneous vomiting occurs hold the victim's head

lower than hips to prevent aspiration.

SPECIAL PROTECTION INFORMATION

Eye Protection: Remove contact lenses and wear chemical safety goggles where contact with liquid

or mist may occur.

Skin Protection: Wear impervious gloves when contact with skin may occur. Use face shields where

splashing may occur.

Inhalation: Use approved respiratory protective equipment for cleaning large spills or entry

into large tanks, vessels or other confined spaces or in situations where exposure

may exceed occupational exposure levels.

Ventilation: Provide adequate ventilation to keep mist or vapors below occupational exposure

levels.

SPILL OR LEAK AND DISPOSAL PROCEDURES

Spill Procedures: Remove sources of heat or ignition including internal combustion engines and

power tools. Remove spill with vacuum trucks or pump and soak up residue with and absorbent. Use approved respirator where occupational exposure limits may

be exceeded.

Waste Disposal:

Dispose through a licensed waste disposal company. Follow federal, state and local

regulation.

SPECIAL PRECAUTIONS AND COMMENTS

Storage Requirements:

Store in tightly closed containers in an dry cool place, away from sources of heat, ignition or strong oxidizers. Ground and bond all transfer and storage equipment and equip with self closing valves, pressure vacuum bungs and flame arresters.

SARA TITLE III INFORMATION

| <u>Acute</u> | Chronic | <u>Fire</u> | <u>Pressure</u> | Reactive |
|--------------|----------------|-------------|-----------------|----------|
|--------------|----------------|-------------|-----------------|----------|

X X

SARA Hazardous Substances

Ingredient CAS NO. %, WT Sec 313 Sec 302 RQ, lb TPQ, lb

None

Key: Sec 313 = Toxic Chemicals, Section 313

Sec 302 = Extremely Hazardous Substances (EHS)

RQ = Reportable Quantity of EHS

TPQ = Threshold Planning Quantity of EHS

CALIFORNIA PROPOSITION 65 WARNING

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in the petroleum products. Although it is possible to sufficiently refine the petroleum products to remove the potential for cancer, we are advising that one or more of the listed chemicals may be present in some detectable quantities. Read and follow directions and use care when handling these petroleum products.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MAKE AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABLENESS AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.