

4318045

Global Parts Order Processing Material Safety Data Sheet MORAN ST. CLAIR CHRYSLER JEEP

C H R Y S L E R
HAZARD COMMUNICATION SHEET

28402 PART/COMMTY CD: 04318045
PREPARATION DATE: 08-23-06 STNDRD: N/AV SUPPLIER: 35573 MFGR: 03500
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: **MASTER SHIELD FABRIC PROTECTOR**
MFG ID : N/AV
DESCRIPTION: PROTECTOR-FABRIC

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS:	PERCENT					
COMM NAME / CAS NO & CHEM NAME:	BY WGT	OSHA	ACGIH	CHRY	UNITS	NOTATIONS
EXISTING INGREDIENTS						
XYLENES	1-5 W	100	100	100	PPM	
001330-20-7 BENZENE, DIMETHYL- (STODDARD SOLVENT)	L	150	150	150		T
008052-41-3 STODDARD SOLVENT (8C ODORLESS MINERAL SPIRITS)	1-5 W	100	100	100	PPM	
064741-65-7 NAPHTHA, PETROLEUM, POLY(DIMETHYLSILOXANE)	60-100 W	300	300	100	PPM	
063148-62-9 SILOXANES AND SILICO	L	400	N/AP	400		
	5-10 W	N/AP	N/AP	N/AP	N/AP	N/AP

GENERIC DESC: FABRIC SHIELD MADE OF SOLVENTS AND POLYMER.

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : 302 F SOLUB IN WATER: NEGLIGIBLE (< 0.1%)
VAPOR PRESSURE: < 1 MM HG AT 68 F EVAP. RATE: 0.090 REF: ETHYL ETHER
VAPOR DENSITY : 4.830 AT N/AV SPECIFIC GRAVITY: 0.820 AT N/AV
PH AT FULL STRENGTH: N/AP PH AT REC. DILUT: N/AP
%VOLATILE BY VOL : 95.0 VOLATILE ORGANIC COMP: N/AV N/AV
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV
APPEARANCE & ODOR: APPEARANCE: CLEAR..... COLOR: COLORLESS..... STATE:
LIQUID.....-ODOR: SOLVENT.....

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

FLASH POINT: 120 F TCC IGN TEMP: N/AP LEL: N/AV UEL: N/AV

SPECIAL FIRE & EXPLOSION HAZARDS:

MAY REACT WITH OXIDIZERS. HEAT PRODUCES HAZARDOUS DECOMPOSITION PRODUCTS.

EXTINGUISHING MEDIA:

DRY CHEMICAL, FOAM EXTINGUISHER, CARBON DIOXIDE, DO NOT USE WATER IN STRAIGHT STREAMS.

SPECIAL FIREFIGHTING PROCEDURES:

USE WATER TO COOL FIRE EXPOSED CONTAINERS. AVOID BREATHING VAPOR OR FUMES.

USE SELF-CONTAINED BREATHING APPARATUS.

SENSITIVE TO MECHANICAL IMPACT?: N/AV SENSITIVE TO STATIC DISCHARGE?: N/AV

HAZARDOUS COMBUSTION PRODUCTS:

N/AV

FLAME PROJECTION: N/AV

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---INGESTION--->> MAY CAUSE UPSET STOMACH, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION (GOING DOWN THE WRONG PIPE INTO THE WINDPIPE) MAY CAUSE THE FOLLOWING: CHEMICAL PNEUMONITIS (AN INFLAMMATION OF THE LUNGS SIMILAR TO PNEUMONIA, WHICH IS CAUSED BY GETTING THE LIQUID FORM OF A CHEMICAL INTO THE LUNGS). <<---EYE CONTACT--->> DIRECT CONTACT-VAPOR AND/OR MIST MAY PRODUCE THE FOLLOWING: IRRITATION AND CONJUNCTIVITIS (AN INFLAMED EYE). <<---SKIN CONTACT--->> CHRONIC EXPOSURE-OR PROLONGED CONTACT MAY PRODUCE THE FOLLOWING: PRIMARY IRRITATION AND DEFATTING AND DRYING OF SKIN. <<---INHALATION--->> HIGH CONCENTRATIONS-VAPOR MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT, DIZZINESS AND NAUSEA. MAY CAUSE REPRODUCTIVE EFFECTS.

EMERGENCY FIRST AID PROCEDURES:

<<---INGESTION--->> CONTACT A PHYSICIAN. DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE LARGE QUANTITIES OF WATER OR MILK. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT LIQUID FROM SEEPING INTO THE WINDPIPE AND LUNGS. <<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. CONTACT A PHYSICIAN. <<---SKIN CONTACT--->> REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. KEEP WARM AND QUIET. IF CONDITION PERSISTS, CONSULT A PHYSICIAN.

*** SECTION 06 - REACTIVITY DATA ***

STABILITY: STABLE

CONDITIONS TO AVOID:

SPARKS OR OPEN FLAME, HIGH TEMPERATURE, FREEZING (DO NOT FREEZE).

MATERIALS TO AVOID:

STRONG OXIDIZING AGENTS.

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

OXIDES OF CARBON MAY BE RELEASED.

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

ELIMINATE ALL IGNITION SOURCES (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC OR FRICTIONAL SPARKS). PROVIDE ADEQUATE VENTILATION. ABSORB ON AN INERT MATERIAL AND REMOVE WITH NON-SPARKING TOOLS. DISCARD INTO SEALED CONTAINERS FOR DISPOSAL. FLUSH AREA WITH WATER.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL REGULATIONS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. ORGANIC VAPOR RESPIRATOR. THIS EQUIPMENT MAY BE REQUIRED. THIS EQUIPMENT MAY BE NEEDED IF THE PRODUCT IS MISTED. OR. THIS EQUIPMENT MAY BE NEEDED IF THE PRODUCT IS SPRAYED..

VENTILATION TYPE:

GOOD GENERAL VENTILATION. THIS EQUIPMENT IS USUALLY ADEQUATE. LOCAL EXHAUST VENTILATION. THIS EQUIPMENT MAY BE REQUIRED.. THIS EQUIPMENT MAY BE NEEDED TO MAINTAIN THE TLV..

PROTECTIVE GLOVES:

RECOMMENDED. VITON GLOVES, NITRILE RUBBER GLOVES OR BUTYL RUBBER GLOVES.

EYE PROTECTION:

RECOMMENDED. CHEMICAL GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS,. THIS EQUIPMENT MAY BE NEEDED IF THE PRODUCT IS MISTED..

OTHER PROTECTIVE EQUIPMENT:

NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS.

*** SECTION 09 - SPECIAL PRECAUTIONS ***

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE IN A COOL, DRY PLACE. USE WITH ADEQUATE VENTILATION. KEEP FROM HEAT, SPARK OR OPEN FLAMES. DO NOT FREEZE. REACTS WITH OXIDIZERS. MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING MIST. AVOID BREATHING VAPOR. AVOID EYE CONTACT. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID INGESTION. WASH THOROUGHLY AFTER HANDLING. REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE REUSE. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. DO NOT INCINERATE. PRODUCT TENDS

Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP

TO MAKE SURFACES, SUCH AS FLOORS, SLIPPERY.

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: 128 HAZARD CLASS - PRMY: ORM-D PACKING GROUP: III

<*> REFER TO EXPLANATIONS PAGE - ITEM D.O.T. FLAMMABLE LIQUIDS.

PROPER SHIPPING NAME: WASTE CONSUMER COMMODITY

LABEL(S) REQUIRED: NONE

RCRA INFORMATION (40 CFR 122-124, 260-265)

WASTE CODE(S)/HZD: D001/I F003/I | MICH:

THE ABOVE INFORMATION IS BASED ON DATA PROVIDED BY SUPPLIERS. TESTING IS NOT
NEEDED